



PIPE SIZE	INSIDE DIAMETER "A"	OUTSIDE DIAMETER "B"	LAYING LENGTH * "C"	OUTSIDE BELL DIAMETER "D"	WALL THICKNESS "E"	APPROX. WEIGHTS
15"	14.875"	19.875"	100"	23"	2.50"	1,109 lbs
18"	18"	23.50"	100"	26.75"	2.75"	1,474 lbs
24"	23.75"	30.75"	100"	32.75"	3.50"	2,402 lbs
30"	29.625"	38.125"	100"	39.50"	4.25"	3,711 lbs
36"	35.875"	44.625"	98"	45.75"	4.375"	4,501 lbs
42"	42"	51.00"	98"	52.25"	4.50"	5,403 lbs
48"	48"	57.875"	98"	58.25"	4.9375"	6,729 lbs
54"	53.875"	64.375"	98"	64.75"	5.25"	8,034 lbs
60"	59.875"	71.875"	96"	74.875"	6.00"	10,500 lbs

\* LAYING LENGTH PER PIPE SIZE VARIES SLIGHTLY, BUT 96" IS TYPICALLY USED FOR RUN CALCULATIONS.

NOT TO SCALE  
DIMENSIONS SUBJECT TO  
SITE SPECIFIC CHANGES.

PRODUCT		DATE	SECTION PAGE
<b>REINFORCED CONCRETE PIPE (CIRCULAR)</b>		01/12/17	01.01